



Hosoe Factory in JAPAN

ALL STAINLESS POWDER COLLECTOR

SP SERIES

The filter can be easily attached and detached by lever operation.

Easy to clean inside the body



■ Specifications

Model		SP-15			SP-30			SP-45			SP-60		
Power supply		50Hz or 60Hz, 3-phase 200V											
Output(kW)		0.75			1.5			2.2			3.7		
Capacity(m ³ /min)		A	B	C	A	B	C	A	B	C	A	B	C
		0	7.5	12.0	0	15.0	28.0	0	22.0	40.0	0	30.0	55.0
Static pressure(kPa)		2.45	1.70	0.69	2.55	2.26	1.27	2.55	2.35	1.37	2.90	2.55	1.22
Noise(dB[A])		65±2 or less									68±2 or less		
Filter	Area(m ²)	4.5			9.0			13.5			18.0		
	Pcs.	1(10 pieces)			2(20 pieces)			3(30pieces)			4(40pieces)		
	Shape/Material	Woven belt / polyester (water washable)											
	Dust removal	Manual shaking type											
Material[Body/Fan]		SUS403/aluminum			SUS304/iron								
Bucket capacity(L)		21			21			42			42		
Power cord(m)		2.8(4-core,without plug)											
Suction port diameter(mm)		φ 127			φ 150			φ 200			φ 200		
W × D × H(mm)	Standard	400 × 650 × 1207			650 × 650 × 1469			850 × 650 × 1497			1180 × 650 × 1660		
	HEPA	400 × 650 × 1500			650 × 650 × 1740			850 × 650 × 1808			1180 × 650 × 1981		
Weight(kg)	Standard	92			145			185			250		
	HEPA	112			170			235			300		

■ Filter

Easy removal of filter by only lever operation without using tools or bolts will save your time spent on dairy cleaning.

The filter can be easily removed by drawing upward from the frame one by one and also wash with water.



Safety Precautions

Please read the instruction manual carefully and use the product correctly.

Specifications and descriptions contained in this catalog may be subject to change without notice.

Please direct any questions to:

AMANO Corporation
 275 MAMEDO-CHO, KOHOKU-KU, YOKOHAMA,
 JAPAN 222-8558
 TEL. +81-45-439-1508 FAX. +81-45-439-1150
 Website: <http://www.amano.co.jp/English>